

/* BFS and DFS Program for GRAPH Traversal */

```
#include<stdio.h>
int q[20],top=-1,front=-1,rear=-1,a[20][20],vis[20],stack[20];
int delete();
void add(int item);
void bfs(int s,int n);
void dfs(int s,int n);
void push(int item);
int pop();

void main()
{
int n,i,s,ch,j;
char c,dummy;
printf("ENTER THE NUMBER VERTICES:");
scanf("%d",&n);
for(i=1;i<=n;i++)
{
for(j=1;j<=n;j++)
{
printf("ENTER 1 IF %d HAS A NODE WITH %d ELSE 0 ",i,j);
scanf("%d",&a[i][j]);
}
}
printf("THE ADJACENCY MATRIX IS\n");
for(i=1;i<=n;i++)
{
for(j=1;j<=n;j++)
{
printf(" %d",a[i][j]);
}
printf("\n");
}

do
{
for(i=1;i<=n;i++)
vis[i]=0;
printf("\nMENU");
printf("\n1.B.F.S");
printf("\n2.D.F.S");
printf("\nENTER YOUR CHOICE");
scanf("%d",&ch);
printf("ENTER THE SOURCE VERTEX :");
scanf("%d",&s);

switch(ch)
{
case 1:bfs(s,n);
```

Pritee Parwekar

```

break;
case 2:
dfs(s,n);
break;
}
printf("DO U WANT TO CONTINUE(Y/N) ? ");
scanf("%c",&dummy);
scanf("%c",&c);
}while((c=='y')||(c=='Y'));
}
void bfs(int s,int n)
{
int p,i;
add(s);
vis[s]=1;
p=delete();
if(p!=0)
printf(" %d",p);
while(p!=0)
{
for(i=1;i<=n;i++)
if((a[p][i]!=0)&&(vis[i]==0))
{
add(i);
vis[i]=1;
}
p=delete();
if(p!=0)
printf(" %d ",p);
}
for(i=1;i<=n;i++)
if(vis[i]==0)
bfs(i,n);
}

```

```

void add(int item)
{
if(rear==19)
printf("QUEUE FULL");
else
{
if(rear== -1)
{
q[++rear]=item;
front++;
}
else
q[++rear]=item;
}
}

```

Pritee Parwekar

```

int delete()
{
int k;
if((front>rear)||((front==1)))
return(0);
else
{
k=q[front++];
return(k);
}
}
void dfs(int s,int n)
{
int i,k;
push(s);
vis[s]=1;
k=pop();
if(k!=0)
printf(" %d ",k);
while(k!=0)
{
for(i=1;i<=n;i++)
if((a[k][i]!=0)&&(vis[i]==0))
{
push(i);
vis[i]=1;
}
k=pop();
if(k!=0)
printf(" %d ",k);
}
for(i=1;i<=n;i++)
if(vis[i]==0)
dfs(i,n);
}
void push(int item)
{
if(top==19)
printf("Stack overflow ");
else
stack[++top]=item;
}
int pop()
{
int k;
if(top==1)
return(0);
else
{
k=stack[top--];
return(k);
}
}

```

}
}